

TOMADA FÊMEA 7 POLOS EM PLÁSTICO PRETA
CÓDIGO: 001100 - 7 POLOS
001700 - 6 POLOS

ENGATCAR

Aplicação:
. Aplicável em todos o modelos de veículos leve com engate para reboque.
Função:
. Ligação elétrica (iluminação) veículo rebocador



Características Técnicas:
Conforme norma ISO 1724
Material:
* Corpo: PAED (Polietileno de Alta Densidade) Preto;
* Polos : Zamac Z5, acabamento zinco branco;
Corrente máxima:
* 2,5mm² - 20A 12vcc;
* 1,5mm²- 15A 12vcc;

Esquema de Ligação:			
POLO	FUNÇÃO	COR DO FIO	
1/L	LUZ DIREÇÃO ESQUERDA	AMARELO	
2/54G	LUZ RÉ	AZUL	
3/31	TERRA	BRANCO	
4/R	LUZ DIREÇÃO DIREITA	VERDE	
5/58R	LANTERNAS E ILUMINAÇÃO DA PLACA	MARROM	
6/54	LUZ FREIO	VERMELHO	
7		LIVRE	

Dimensões:

Top view technical drawing of a circular connector. The drawing shows a central circular body with a flange. The main body has a diameter of $\varnothing 36,50$. The flange has a diameter of $\varnothing 56$. There are four mounting holes on the flange, each with a diameter of $\varnothing 5,6$. The distance between the centers of two opposite mounting holes is $\varnothing 10,50$. The angle between the centers of two adjacent mounting holes is 120° . A central cylindrical protrusion is shown with a diameter of $\varnothing 10,50$.

Side view technical drawing of the connector. The drawing shows the profile of the connector, including the main body and the flange. The height of the main body is $72,50$. The width of the main body is $43,20$. The width of the flange is $45,9$. The flange is shown in a slightly angled position, indicating its flexibility.